

ULTRATAINER® IBC

Unique cylindrical tank design eliminates corners, ribs and seams, and lends itself well to mixing and cleaning operations. Each tank is designed for easy, safe handling and has forklift and stacking capability.

FEATURES:

- UN/DOT Certified (31H1)
- Packaging Group II and III per Title 49 CFR
- ½" wall thickness HDPE
- 1.9 Specific Gravity
- Pressure rated to 15 PSI
- 6" screw cap with security tether
- 2" plastic vacuum relief vent
- Two 2" bungs in the top of the tank
- 2" standard port male camlock bottom drain valve with dust cap
- Molded-in and inked gallonage markers
- Forklift and stacking capability

OPTIONS:

- 20" lid opening for applications requiring more access to tank's interior for mixing or cleaning
- Heavy weight (62 PSI) option available
- Optional retractable lifting lugs offer superior top-lifting capacity with crane-hook attachments
- Teeter bars
- Tamper-evident capability



SPECIFICATIONS

CAPACITY* [US GALLONS]	TARE WT*	LENGTH*	WIDTH*	HEIGHT*
220	268 lbs	46"	46"	54"
275	289 lbs	46"	46"	62"
330	309 lbs	46"	46"	70"

*All dimensions, gallons, and weights are nominal.

** Tare weights quoted do not include top lift.



Believe in better service.

PRECISIONIBC.COM

BROUSSARD, LA
888.805.1247

FAIRHOPE, AL
800.544.7069

DEC '17